

# Product Information Sheet


<b>PRODUCT NAME</b>	<b>PRODUCT CODE</b>
antenna GSM - UNI	40607

## Electrical Characteristics

1	Frequency Range	GSM900:820-960MHZ
		GSM1800:1710-1880MHZ
		GSM1900:1850-1990MHZ
		UMTS:1900-2170MHZ
2	V.S.W.R	3.0:1
3	Band Width	140MHZ@900MHZ
		170MHZ@1800MHZ
		140MHZ@1900MHZ
		270MHZ@2000MHZ
4	Impedence	50 ohm
5	Gain(Typical)	0dbi@900MHZ
		1dbi@1800MHZ
		1dbi@1900MHZ
		1.5dbi@2000MHZ
6	Azimuth	Omni-direction
7	Polarization	Linear polarization

## Material

No	Part Name	SPEC
1	Antenna	PCB
2	RF Cable	RG174 ( L=3±0.1M )
3	RF Connector	UNI (without connector)
4	Mounting	Adhesive Type
5	Enclosures	Plastic
6	Thickness	6mm(Typical)



## Testing Conditions

1	Working Temp	-45°C~+85°C
2	Storage Temp	-45°C~+85°C
3	Vibration	Sine sweep 1g(0-p)
		10~55~10Hz each axis

## Notes



## Structure

